

Full IP65 Chassis LCD

19"

Specifications



| | |
|--------------------------------|--|
| Model Name | R19L300-65M1 |
| Viewable Size Image | 19" |
| Active Display Area(mm) | 376.32 (H) x 301.06 (V) |
| Pixel Pitch(mm) | 0.294 (H) x 0.294 (V) |
| Number of Pixels | 1280x1024 |
| Contrast Ratio | 800:1(typ.) |
| Display Color | 16.7M(8bit+FRC) |
| Brightness(cd/m ²) | 300(typ.) |
| Viewing Angle(CR>=10) | -80~80(H);-80~80(V)(typ.) |
| Synchronization Range | |
| Horizontal/Vertical | 31.5~80.0KHz / 60~75Hz |
| Recommended Resolution | 1280x1024@60HZ,75HZ |
| Signal Connector | 15 pin D-Sub |
| I/O | 3-in-1 power/RS232/usb cable (IP65 connector in monitor side) VGA cable (IP65 connector in monitor side) |
| Power Source | DV12 |
| Power Consumption | 41W typical, normal operation |
| Power Management | VESA DPMS Compliant |
| Plug & Play | VESA DDC 1/2B |
| Optional Video Input | No |
| Optional DVI Input | No |
| Optional Touch Screen | Resistive,Capacitive,SAW(IP54 only) |
| Net Weight (kg)(without touch) | 5.1 |



*Due to Panel material's deviation, different panel supplier will set different specific variance range to optical characteristics. The factors of time used, Lamp current, Ambient temperature will influence the optical measurements.

Mechanical Drawing

* Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.