

Full HD(1080P) Resolution Video Wall Box

New HDMI Solution



Model	iVW-FH122		iVW-FD122		iVW-FD133		
Features	<ul style="list-style-type: none"> iNDS unique GeniMask™ bezel masking technology Support up to 1920 x 1200 input content 1 x Full screen HDMI output and 1 set of 2x2 HDMI output Output timing 720p/1080p Support multiple display modes, such as full mode, clone mode, and User mode etc. Audio output via HDMI cable and extra 2 channels analog output, 1 x SPDIF output Allow remote managing via RJ-45, RS-232 cable or USB cable 		<ul style="list-style-type: none"> iNDS unique GeniMask™ bezel masking technology Support up to 1920 x 1200 input content Support multiple display modes, such as full mode, clone mode, etc. Allow remote managing via RS-232 cable or DVI cable Easy-to-DIY video wall solution 		<ul style="list-style-type: none"> iNDS unique GeniMask™ bezel masking technology Support up to 1920 x 1200 input content Support multiple display modes, such as full mode, clone mode, etc. Allow remote managing via RS-232 cable or DVI cable Easy-to-DIY video wall solution 		
Dimensions (mm)	156 x 169 x 60 (W x D x H)		230 x 180 x 47 (W x D x H)		295 x 188 x 47 (W x D x H)		
Cooling	Internal Fan		Fanless		Fanless		
Front Panel	LED Light	6 x LED (1 x Input, 4 x Output, 1 x Power)		6 x LED (1 x Input, 4 x Output, 1 x Power)		11 x LED (1 x Input, 9 x Output, 1 x Power)	
	Keypad	6 Keys		6 Keys		6 Keys	
	IR Receiver	Yes		Yes		Yes	
Rear Panel	Input	1 x HDMI input		1 x DVI-D single-link input		1 x DVI-D single-link input	
	Output	2 channels analog output via 9 pins connector, 1 x SPDIF connector 1 x Full screen HDMI output 1 set of 2x2 HDMI output (HDCP supported)		4 x DVI-D single-link output		9 x DVI-D single-link output	
	RS-232	1 x RS-232 (Via RJ-45 Connector) 1 x RJ-45 (for Ethernet), 1 x mini USB		1 x RS-232		1 x RS-232	
Resolution	Clone mode, Full mode, Vertical replication mode, PIP mode, User mode		Clone mode, Full mode, Vertical replication mode, PIP mode		Clone mode, Full mode (3x3, 3x2, 2x3, 2x2)		
	Input	Output	Input	Output	Input	Output	
	Up to 1920 x 1200 640 x 400 (70 Hz) 720 x 400 (70 / 85 Hz) 640 x 480 (60 / 66 / 70 / 72 / 75 Hz) 800 x 600 (56 / 60 / 66 / 70 / 72 / 75 Hz) 1024 x 768 (60 / 66 / 70 / 72 / 75 Hz) 1280 x 720 (60 Hz) 1280 x 768 (60 Hz) 1360 x 768 (60 Hz) 1366 x 768 (60 Hz) 1152 x 864 (75 Hz) 1280 x 960 (60 Hz) 1280 x 1024 (60 / 70 / 75 Hz) 1600 x 1200 (60 Hz) 480p 720p 1080i/p 1920 x 1200 (60 Hz)	720p/1080p	640 x 480 800 x 600 1024 x 768 1280 x 768 1360 x 768 1366 x 768 1400 x 1050 1680 x 1050 1600 x 1200 1920 x 1080 1280 x 960 1280 x 1024 1680 x 1050 1600 x 1200 1920 x 1080 1920 x 1200	1024 x 768 1360 x 768 1366 x 768 1280 x 1024 1400 x 1050 1680 x 1050 1600 x 1200 1920 x 1080 1280 x 960 1280 x 1024 1680 x 1050 1600 x 1200 1920 x 1080 1920 x 1200	640 x 480 800 x 600 1024 x 768 1280 x 768 1360 x 768 1366 x 768 1400 x 1050 1680 x 1050 1600 x 1200 1920 x 1080 1280 x 960 1280 x 1024 1680 x 1050 1600 x 1200 1920 x 1080 1920 x 1200	1024 x 768 1360 x 768 1366 x 768 1280 x 1024 1400 x 1050 1680 x 1050 1600 x 1200 1920 x 1080 1280 x 960 1280 x 1024 1680 x 1050 1600 x 1200 1920 x 1080 1920 x 1200	
Power Consumption	24W		20W		35W		
Power Supply	Connector	DC Power Jack		DC Power Jack		DC Power Jack	
	Input	90VAC to 264VAC/47Hz to 63Hz		90VAC to 264VAC/47Hz to 63Hz		90VAC to 264VAC/47Hz to 63Hz	
	Output	12V DC		12V DC		12V DC	
OSD Function	1. Power On/Off 2. Output resolution selection 3. GeniMask bezel masking control		1. Power On/Off 2. Output resolution selection 3. GeniMask bezel masking control		1. Power On/Off 2. Output resolution selection 3. GeniMask bezel masking control		
Temperature	0°C ~ 40°C		0°C ~ 40°C		0°C ~ 40°C		
Safety and Emission	CE, FCC, and CCC		CE, FCC, and CCC		CE, FCC, and CCC		

Hertz: Screen Refresh Rate.

1
IEI Mobile Solutions

2
Automation Panel Solutions

3
Video Wall Controller/ Splitter

4
RISC-based Solutions

5
PACsmate Medical Solutions

6
Optional Peripherals

Ultra High Resolution Video Wall Box(above 1080P)



New



New



New

Model	iVW-UD112			iVW-UD212			iVW-UD322			
Features	<ul style="list-style-type: none"> • Easy-to-install, flexible combination, cost-effective solution • High-resolution display content input and output • Non-scaling, pixel-to-pixel mapping advantage • Support various display modes • iNDS unique GeniMask™ bezel masking technology 			<ul style="list-style-type: none"> • Easy-to-install, flexible combination, cost-effective solution • High-resolution display content input and output • Non-scaling, pixel-to-pixel mapping advantage • Support various display modes • iNDS unique projection blending technology 			<ul style="list-style-type: none"> • Easy-to-install, flexible combination, cost-effective solution • High-resolution display content input and output • Non-scaling, pixel-to-pixel mapping advantage • Support various display modes • iNDS unique GeniMask™ bezel masking technology • High Frame Rate 			
Dimensions (mm)	230 x 130 x 47			230 x 135 x 53			229.5 x 178.2 x 47			
Cooling	Fanless			Fanless			Fanless			
Front Panel	LED Light	1 x LED (1 x Power)			4 x LED (1 x Input, 2 x Output, 1 x Power)			6 x LED (1 x Input, 4 x Output, 1 x Power)		
	Keypad	5 Keys			6 Keys			6 Keys		
	IR Receiver	Yes			Yes			Yes		
Rear Panel	Input	1 x DVI-D dual link / DVI-A single link (VGA to DVI-I) input			1 x DVI-D dual-link input			1 x DVI-D dual-link input		
	Output	2 x DVI-D Single-link Output			2 x DVI-D single-link Output			4 x DVI-D single-link Output		
	Power Switch	1 x Power(In) with lock			1 x Power (In) with lock			1 x Power (In) with lock		
RS-232	N/A			1 x RS-232			1 x RS-232			
Resolution	Input	Output	Output Vertical Frequency (Hz)	Input	Output	Output Vertical Frequency (Hz)	Input	Output	Output Vertical Frequency (Hz)	
	Full mode (2 x 1)			Full mode 2x1, Blending 1/4			Full mode (2 x 2)			
	1600 x 480	2 x 800 x 480	60	1400 x 480	2 x 800 x 480	60	2048 x 1536	4 x 1024 x 768	60	
	1600 x 600	2 x 800 x 600	60	1400 x 600	2 x 800 x 600	60	2560 x 2048	4 x 1280 x 1024	60	
	2048 x 768	2 x 1024 x 768	50	1792 x 768	2 x 1024 x 768	60	2560 x 1440	4 x 1280 x 720	60	
	2560 x 720	2 x 1280 x 720	50	2240 x 720	2 x 1280 x 720	60	2560 x 1600	4 x 1280 x 800	60	
	2560 x 768	2 x 1280 x 768	60	2240 x 768	2 x 1280 x 768	60	2720 x 1536	4 x 1360 x 768	60	
	2560 x 800	2 x 1280 x 800	50	2240 x 800	2 x 1280 x 800	60	3840 x 2880	4 x 1920 x 1440	60	
	2560 x 1024	2 x 1280 x 1024	50	2240 x 1024	2 x 1280 x 1024	60	3840 x 2160	4 x 1920 x 1080	60	
	2720 x 768	2 x 1360 x 768	60	2380 x 768	2 x 1360 x 768	60	3840 x 2400	4 x 1920 x 1200	60	
	2880 x 900	2 x 1440 x 900	50	2520 x 900	2 x 1440 x 900	60	2560 x 1920	4 x 1280 x 960	60	
	2800 x 1050	2 x 1400 x 1050	50	2450 x 1050	2 x 1400 x 1050	60	1280 x 960	4 x 640 x 480	60	
	3200 x 1200	2 x 1600 x 1200	48	2800 x 1200	2 x 1600 x 1200	60	3392 x 1920	4 x 1696 x 960	60	
	3360 x 1050	2 x 1680 x 1050	50	2940 x 1050	2 x 1680 x 1050	60	1696 x 960	4 x 848 x 480	60	
	3840 x 1080	2 x 1920 x 1080	49	3360 x 1080	2 x 1920 x 1080	60	2732 x 1536	4 x 1366 x 768	60	
	3840 x 1200	2 x 1920 x 1200	48	3360 x 1200	2 x 1920 x 1200	60	Vertical replication mode (2 x 1)			
	4096 x 1536	2 x 2048 x 1536	30	Full mode 2 x 1, Blending 1/8			2560 x 1024	2 x 1280 x 1024	60	
	Clone mode (1x1)			1500 x 480	2 x 800 x 480	60	3840 x 1080	2 x 1920 x 1080	60	
	800 x 600	1 x 800 x 600	60.32	1500 x 600	2 x 800 x 600	60	3840 x 1200	2 x 1920 x 1200	60	
	1024 x 768	1 x 1024 x 768	60	1920 x 768	2 x 1024 x 768	60	Clone mode (1 x 1)			
	1280 x 720	1 x 1280 x 720	60	2400 x 720	2 x 1280 x 720	60	1024 x 768	1 x 1024 x 768	60	
	1280 x 768	1 x 1280 x 768	59.87	2400x768	2 x 1280 x 768	60	Full mode (4 x 1)			
	1280 x 800	1 x 1280 x 800	60	2400 x 800	2 x 1280 x 800	60	3392 x 480	4 x 848 x 480	60	
	1360 x 768	1 x 1360 x 768	60.02	2400 x 1024	2 x 1280 x 1024	60	3200 x 600	4 x 800 x 600	60	
	1400 x 1050	1 x 1400 x 1050	59.98	2550 x 768	2 x 1360 x 768	60	3840 x 600	4 x 960 x 600	60	
	1440 x 900	1 x 1440 x 900	59.89	2700 x 900	2 x 1440 x 900	60	4094 x 768	4 x 1024 x 768	60	
	1680 x 1050	1 x 1680 x 1050	59.88	2625 x 1050	2 x 1400 x 1050	60	Full mode (3 x 1)			
	1920 x 540	1 x 1920 x 540	25	3000 x 1200	2 x 1600 x 1200	60	3072 x 768	3 x 1024 x 768	60	
	720 x 480	1 x 720 x 480	59.94	3150 x 1050	2 x 1680 x 1050	60	3840 x 800	3 x 1280 x 800	60	
				3600 x 1080	2 x 1920 x 1080	60	3840 x 1024	3 x 1280 x 1024	60	
				3600 x 1200	2 x 1920 x 1200	60	4080 x 768	3 x 1360 x 768	60	
				Clone mode 1 x 1			Full mode (1 x 4)			
			800 x 600	1 x 800 x 600	60.32	1024 x 3072	4 x 1024 x 768	60		
			1024 x 768	1 x 1024 x 768	60	1280 x 3200	4 x 1280 x 800	60		
			1280 x 720	1 x 1280 x 720	60	1280 x 4095	4 x 1280 x 1024	60		
			1280 x 768	1 x 1280 x 768	59.87	1360 x 3072	4 x 1360 x 768	60		
			1280 x 800	1 x 1280 x 800	60	1366 x 3072	4 x 1366 x 768	60		
			1280 x 1024	1 x 1280 x 1024	60.02	Full mode (1 x 3)				
			1360 x 768	1 x 1360 x 768	60.02	1024 x 2304	3 x 1024 x 768	60		
			1440 x 900	1 x 1440 x 900	59.89	1280 x 2400	3 x 1280 x 800	60		
			1400 x 1050	1 x 1400 x 1050	59.98	1280 x 3072	3 x 1280 x 1024	60		
			1600 x 1200	1 x 1600 x 1200	60	1360 x 2304	3 x 1360 x 768	60		
			1680 x 1050	1 x 1680 x 1050	59.88	1366 x 2304	4 x 1366 x 768	60		
			1920 x 1080	1 x 1920 x 1080	60					
			1920 x 1200	1 x 1920 x 1200	59.88					
Power Consumption	17W			25W			18W			
Power Connector	DC Power Jack			DC Power Jack with lock			DC Power Jack			
Power Supply Input	90VAC to 264VAC/47Hz to 63Hz			AC100~240V input to DV 12V output			90VAC to 264VAC/47Hz to 63Hz			
Power Supply Output	5V DC						12V DC			
OSD Function	<ol style="list-style-type: none"> 1. Power On/Off 2. Output resolution selection 3. GeniMask bezel masking control 			<ol style="list-style-type: none"> 1. Power On/Off 2. Output resolution selection 3. Projection blending control 			<ol style="list-style-type: none"> 1. Power On/Off 2. Output resolution selection 3. GeniMask bezel masking control 			
Temperature	0°C ~ 40°C			0~40°C			0~40°C			
Safety and Emission	CE, FCC, and CCC			CE, FCC, and CCC			CE, FCC, and CCC			

1

IEI Mobile Solutions

2

Automation Panel Solutions

3

Video Wall Controller/ Splitter

4

RISC-based Solutions

5

PACSmate Medical Solutions

6

Optional Peripherals

Ultra High Resolution Video Wall Box (above 1080P)



New



New

Model	iVW-UD124			iVW-UD133			iVW-UD144			
Features	<ul style="list-style-type: none"> • Easy-to-install, flexible combination, cost effective solution • High-resolution display content input and output • Non-scaling, pixel-to-pixel mapping advantage • Support various display modes • iNDS unique GeniMask™ bezel masking technology 			<ul style="list-style-type: none"> • Easy-to-install, flexible combination, cost effective solution • High-resolution display content input and output • Non-scaling, pixel-to-pixel mapping advantage • Support various display modes • iNDS unique GeniMask™ bezel masking technology 			<ul style="list-style-type: none"> • Easy-to-install, flexible combination, cost effective solution • High-resolution display content input and output • Non-scaling, pixel-to-pixel mapping advantage • Support various display modes • iNDS unique GeniMask™ bezel masking technology 			
Dimensions (mm)	370 x 190 x 48			295 x 188 x 47			370 x 190 x 95			
Cooling	Fanless			Fanless			Fanless			
Front Panel	LED Light	10 x LED (1 x Input, 8 x Output, 1 x Power)			11 x LED (1 x Input, 9 x Output, 1 x Power)			18 x LED (1 x Input, 16 x Output, 1 x Power)		
	Keypad	6 Keys			6 Keys			6 Keys		
	IR Receiver	Yes			Yes			Yes		
Rear Panel	Input	1 x DVI-D dual-link input			1 x DVI-D dual-link input			1 x DVI-D dual-link input		
	Output	8 x DVI-D single-link Output			9 x DVI-D single-link Output			16 x DVI-D single-link Output		
	Power Switch	1 x Power (In) with lock			1 x Power (In) with lock			1 x Power (In) with lock		
	RS-232	1 x RS-232			1 x RS-232			1 x RS-232		
Resolution	Input	Output	Output Vertical Frequency (Hz)	Input	Output	Output Vertical Frequency (Hz)	Input	Output	Output Vertical Frequency (Hz)	
	Full mode (4 x 2)			Full mode (3 x 3)			Full mode (4 x 4)			
	3392 x 960	8 x 848 x 480	60	3072 x 2304	9 x 1024 x 768	60	3392 x 1920	16 x 848 x 480	60	
	3200 x 1200	8 x 800 x 600	60	3840 x 2160	9 x 1280 x 720	66	3200 x 2400	16 x 800 x 600	60	
	3840 x 1200	8 x 960 x 600	60	3840 x 2400	9 x 1280 x 800	58	3840 x 2400	16 x 960 x 600	60	
	4094 x 1536	8 x 1024 x 768	60	3840 x 3072	9 x 1280 x 1024	60	4094 x 3072	16 x 1024 x 768	60	
	Full mode (3 x 2)			4080 x 2304	9 x 1360 x 768	57	Full mode (4 x 3)			
	3072 x 1536	6 x 1024 x 768	60	Full mode (2 x 3)			3392 x 1440	12 x 848 x 480	60	
	3840 x 1600	6 x 1280 x 800	60	2048 x 2304	6 x 1024 x 768	60	3200 x 1800	12 x 800 x 600	60	
	3840 x 2048	6 x 1280 x 1024	60	2560 x 2400	6 x 1280 x 800	58	3840 x 1800	12 x 960 x 600	60	
	4080 x 1536	6 x 1360 x 768	60	2560 x 3072	6 x 1280 x 1024	60	4094 x 2304	12 x 1024 x 768	60	
	Full mode (2 x 4)			2720 x 2304	6 x 1360 x 768	57	Full mode (3 x 4)			
	2048 x 3072	8 x 1024 x 768	60	Full mode (3 x 2)			3072 x 3072	12 x 1024 x 768	60	
	2560 x 3200	8 x 1280 x 800	60	3072 x 1536	6 x 1024 x 768	60	3840 x 3200	12 x 1280 x 800	60	
	2560 x 4095	8 x 1280 x 1024	60	3840 x 1600	6 x 1280 x 800	58	3840 x 4095	12 x 1280 x 1024	60	
	2720 x 3072	8 x 1360 x 768	60	3840 x 2048	6 x 1280 x 1024	60	4080 x 3072	12 x 1360 x 768	60	
	Full mode (2 x 3)			4080 x 1536	6 x 1360 x 768	57	4094 x 3072	12 x 1366 x 768	60	
	2560 x 3072	6 x 1280 x 1024	60				Full mode (3 x 3)			
	3200 x 3600	6 x 1600 x 1200	60				3072 x 2304	9 x 1024 x 768	60	
	3840 x 3240	6 x 1920 x 1080	60				3840 x 2160	9 x 1280 x 720	60	
	3840 x 3600	6 x 1920 x 1200	60				3840 x 2400	9 x 1280 x 800	60	
							3840 x 3072	9 x 1280x1024	60	
							4080 x 2304	9 x 1360 x 768	60	
							4094 x 2304	9 x 1366 x 768	60	
						Full mode (3 x 2)				
						3072 x 1536	6 x 1024 x 768	60		
						3840 x 1600	6 x 1280 x 800	60		
						3840 x 2048	6 x 1280 x 1024	60		
						4094 x 1536	6 x 1366 x 768	60		
						Full mode (2x3)				
						2048 x 2304	6 x 1024 x 768	60		
						2560 x 2400	6 x 1280 x 800	60		
						2560 x 3072	6 x 1280 x 1024	60		
						2732 x 2304	6 x 1366 x 768	60		
Power Consumption	25W			17W			22W			
Power Supply	Connector	DC Power Jack			DC Power Jack			DC Power Jack		
	Input	90VAC to 264VAC / 47Hz to 63Hz			90VAC to 264VAC/47Hz to 63Hz			90VAC to 264VAC/47Hz to 63Hz		
	Output	12V DC			12V DC			12V DC		
OSD Function	<ol style="list-style-type: none"> 1. Power On/Off 2. Output resolution selection 3. GeniMask bezel masking control 			<ol style="list-style-type: none"> 1. Power On/Off 2. Output resolution selection 3. GeniMask bezel masking control 			<ol style="list-style-type: none"> 1. Power On/Off 2. Output resolution selection 3. GeniMask bezel masking control 			
Temperature	0~40°C			0°C ~ 40°C			0~40°C			
Safety and Emission	CE, FCC, and CCC			CE, FCC, and CCC			CE, FCC, and CCC			

1
IEI Mobile Solutions

2
Automation Panel Solutions

3
Video Wall Controller/ Splitter


4
RISC-based Solutions

5
PACsmate Medical Solutions

6
Optional Peripherals

Unique GeniMASK™ Technology

GeniMASK™ adjusts the mask settings of all the video box controllers. Adjusting each video box individually is time-consuming, but with GeniMASK™ technology, and the included remote control, the mask settings can be adjusted at once as easy as changing TV channels. No separate adjustment is needed. Set once and it's done!



1

IEI Mobile Solutions

2

Automation Panel Solutions

3

Video Wall Controller/ Splitter

4

RISC-based Solutions

5

PACSmate Medical Solutions

6

Optional Peripherals

GeniMASK™ Adjustment

iNDS provides three utilities to adjust the mask setting. Turn on the "Mask Control" and set up the "Mask Value".


1. By IR Remote Control



3. By Smart Software OSD (via DDC/RS-232 interface)




For iVW-FH122/FD122/FD133




For iVW-UD112/UD212/UD322/UD124/UD133/UD144

2. By Hardware OSD Keypad




(Hotkeys for iVW-FD122/FD133)

- Factory reset : Left+Auto
- Lock /Unlock key: Right +Auto)



iSignager Video Wall System



Quick Allocation of Video Wall Display Content


For General User

Design customized layout by iSignager AdDesign V4.x software

The iNDS digital signage software "iSignager AdDesign V4.x" allows multiple content layout design. It is usable to create a multiple layout for video wall application. Users can easily build the single or traversed or even independent media zones.

- Video wall setup**
- Resolution setting
 - Arrangement setting

- Video wall content design**
- Full screen single image
 - Allocate the layout of multiple images



1
IEI Mobile Solutions

2
Automation Panel Solutions

3
Video Wall Controller/ Splitter

4
RISC-based Solutions

5
PACsmate Medical Solutions

6
Optional Peripherals

Support Various Display Modes


Full HD Resolution

Full Mode

Image is spread over the entire display array.



**iVW-FD122 &
iVW-FH122 (2 x 2)**




iVW-FD133 (3 x 3, 2 x 3, 3 x 2, 2 x 2)

Clone Mode

Vertical Replication Mode

1


IEI Mobile Solutions



**iVW-FD122 &
iVW-FH122 (1 x 1)**

iVW-FD133 (1 x 1)

Same content on four screens



**iVW-FD122 &
iVW-FH122 (2 x 1)**

Display the same image in rows, for implementing wide video walls

2

Automation Panel Solutions

3

Video Wall Controller/ Splitter

4

RISC-based Solutions


5

PACSmate Medical Solutions

6

Optional Peripherals

PIP Mode (for iVW-FD122 & iVW-FH122)



Mode 1

Full image on the upper-left screen

Mode 2

Full image on the upper-right screen

Mode 3

Full image on the lower-left screen

Mode 4

Full image on the lower-right screen

Support Various Display Modes

Ultra High Resolution


» According to the final image, set up the monitors in sequence

*Remark: The number is the DVI output port number on iVW for 90° clockwise rotation video wall setup, and the number in () is for 90° counterclockwise rotation. The rotation may vary depending on the support of graphic card & its driver.




iVW-UD322


Landscape (2x2)




Portrait* (2x2)




* Portrait Monitor (3x1) / Horizontal Span



* Portrait Monitor (4x1) / Horizontal Span




Landscape Monitor (1x4) / Vertical Span




* Portrait Monitor (1x4) / Vertical Span

Landscape Monitor (3x1) / Horizontal Span



* Portrait Monitor (1x3) / Vertical Span



Landscape Monitor (4x1) / Horizontal Span




iVW-UD133


Landscape (3x3)




Landscape (2x3)




Landscape (3x2)




Portrait* (3x3)





Portrait* (3x2)






Portrait* (2x3)



iVW-UD112



iVW-UD212



1
IEI Mobile Solutions

2
Automation Panel Solutions

3
Video Wall Controller/ Splitter

4
RISC-based Solutions

5
PACSmate Medical Solutions

6
Optional Peripherals

Support Various Display Modes

Ultra High Resolution



iVW-UD144



iVW-UD124

Landscape 4x4

1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16

Portrait* 4x4

13 (4)	9 (8)	5 (12)	1 (16)
14 (3)	10 (7)	6 (11)	2 (15)
15 (2)	11 (6)	7 (10)	3 (14)
16 (1)	12 (5)	8 (9)	4 (13)

Landscape 4x2

1	2	3	4
5	6	7	8

Portrait* 2x4

5 (4)	1 (8)
6 (3)	2 (7)
7 (2)	3 (6)
8 (1)	4 (5)

Landscape 4x3

1	2	3	4
5	6	7	8
9	10	11	12

Landscape 3x2

1	2	3
5	6	7

1

IEI Mobile Solutions

Landscape 3x4

1	2	3
4	5	6
7	8	9
10	11	12

Portrait* 3x4

9 (4)	5 (8)	1 (12)
10 (3)	6 (7)	2 (11)
11 (2)	7 (6)	3 (10)
12 (1)	8 (5)	4 (9)

Landscape 2x4

1	2
5	6
3	4
7	8

Portrait* 2x3

5 (3)	1 (6)
6 (2)	2 (6)
7 (1)	3 (4)

2

Automation Panel Solutions

Landscape 3x3

1	2	3
4	5	6
7	8	9

Landscape 2x3

1	2
5	6
3	4

Portrait* 4x2

7 (2)	3 (6)	5 (4)	1 (8)
8 (1)	6 (5)	4 (3)	2 (7)

4

RISC-based Solutions

Landscape 3x2

1	2	3
4	5	6

Portrait* 4x3

10 (3)	7 (6)	4 (9)	1 (12)
11 (2)	8 (5)	5 (8)	2 (11)
12 (1)	9 (4)	6 (7)	3 (10)

5

PACSmate Medical Solutions

Landscape 2x3

1	2
3	4
5	6

Portrait* 3x2

3 (2)	5 (6)	1 (4)
4 (1)	6 (5)	2 (3)

6

Optional Peripherals